



## Weguard

Safe deposit box

Technical file



SPARE PARTS



RECYCLED  
MATERIAL



RECYCLABLE

### Description

#### Frame

Made with polypropylene resins and recycled material 3,5 mm thick.  
Reinforced with mineral filler and a special formulation with UV treatment.

#### Closure

Mainly made of ABS.  
Suitable for outdoor use and high resistance to salinity.

#### Screws

ISO 7380 M6x20 screws and M6 DIN 985 nuts made of stainless steel.





## Weguard

### Safe deposit box

#### Capacity



A

C

A - 28 cm  
B - 8,5 cm

C - 20 cm  
D - 8,5 cm

Package	Units	Measures	Weight	Volume
Weguard	1 u.	28x20x8,5 cm	0,53 kg	0,004 m <sup>3</sup>
Weguard with key	1 u.	28x20x8,5 cm	0,62 kg	0,004 m <sup>3</sup>
Box	20 u.	80x56x20 cm	13,4 kg	0,09 m <sup>3</sup>
Pallet	400 u.	120x80x214 cm	295 kg	2,05 m <sup>3</sup>

Loading capacity	Mega trailer	Cont. 20'	Cont. 40'	Cont. 40' High Cube
Weguard	13.200 u.	4.400 u.	10.000 u.	11.000 u.

#### Finishes

##### Frame

##### Resin





## Weguard

Safe deposit box

---

### Maintenance plan

---

#### Weekly

Visual check of the general condition, removing dirt and ensuring there are no broken parts or damage that could be a danger to users.

#### Monthly

Check the correct operation of the numeric dials.

Check the structural strength and stability.

#### Annual

Check the good condition of the product.

Replace any worn or damaged parts.

#### Wintering and storage

Clean with soapy water and a soft cloth.

Remove damp stains, sand and seawater.

Lubricate the inside of the lock if necessary.

#### Observations

- Always use Balliu spare parts.
- Balliu does not manufacture parts for other brands.
- If the product is subject to heavy use, maintenance checks must be carried out more frequently.
- Do not use the product until maintenance is completed.
- Do not use aggressive chemicals to clean the product.
- Always use products with a neutral pH.
- Use a soft cloth to clean the product.

